



Specifications Ledvance LED Downlight Biolux DN150  
20W 1800lm 60D - 927-965 Tunable White | 175,4mm  
- Cutout 165mm - Zigbee Dimmable - Best Colour  
Rendering

[View Product](#)

## General Information

|                          |                               |
|--------------------------|-------------------------------|
| SKU                      | 237918                        |
| EAN                      | 4058075400733                 |
| Brand                    | Ledvance                      |
| Manufacturer Name        | BIOLUX HCL DL DN150 ZB 20W TW |
| Any Lamp all-in warranty | 5 Years                       |
| Average Lifetime (h)     | 50000                         |

## Technical Information

|                             |                                      |
|-----------------------------|--------------------------------------|
| Emergency Lighting          | No Emergency Unit                    |
| Tiltable                    | No                                   |
| Technology                  | LED Integrated                       |
| Wattage                     | 20                                   |
| Voltage (V)                 | 220-240                              |
| Dimmable                    | Dimmable                             |
| Colour Code                 | 927 Extra Warm White, 965 Daylight   |
| Colour temperature (Kelvin) | 2700 Extra Warm White, 6500 Daylight |
| Colour Rendering (Ra)       | 90-99                                |
| Colour of Light             | White                                |
| Light colour options        | Tunable White                        |
| Including bulb              | Yes                                  |

|                          |                                       |
|--------------------------|---------------------------------------|
| Driver Included          | Yes                                   |
| Beam Angle (degree)      | 60                                    |
| Luminous Flux (Lumen)    | 1800                                  |
| Luminous Efficacy (lm/W) | 90                                    |
| Power factor             | >0.90                                 |
| Installation Depth (mm)  | 150                                   |
| Unified Glare Rating     | < 28 - for hallways and storage rooms |
| Optical Cover            | PC (Polycarbonate)                    |
| Finish of Reflector      | PC (Polycarbonate)                    |
| Product Type Category    | LED Downlight                         |

## Fixture Information

|                       |            |
|-----------------------|------------|
| Cut out (mm)          | 165        |
| IP-rating             | IP20       |
| Operating Temperature | -20 to +40 |
| Housing               | Aluminium  |
| Colour of the Fixture | White      |
| Series                | BIOLUX     |

## Dimensions

|               |       |
|---------------|-------|
| Height (mm)   | 98.9  |
| Diameter (mm) | 175.4 |

## Why Any-lamp?

## Sensor Information


 Order from the **largest lighting specialist** in Europe


**Customised** quotation

Type of sensor
 

 No Sensor


 Up to **7 years warranty**


**Easy** return process