



Specifications Noxion LED Downlight
Apollo 9W 1100lm 60D - 840 Cool
White | 145mm - Cutout 120mm - UGR
<19



[View Product](#)

General Information

| | |
|--------------------------|---|
| SKU | 243079 |
| EAN | 8719157034982 |
| Brand | Noxion |
| Manufacturer Name | Noxion LED Downlight Apollo 9W 1200LM 4000K Cutout Ø120mm Frame Ø145mm |
| Any Lamp all-in warranty | 6 Years |
| Average Lifetime (h) | 60000 |

Technical Information

| | |
|-----------------------------|-------------------|
| Emergency Lighting | No Emergency Unit |
| Tiltable | No |
| Technology | LED Integrated |
| Voltage (V) | 220-240 |
| Dimmable | Not Dimmable |
| Colour Code | 840 Cool White |
| Colour temperature (Kelvin) | 4000 Cool White |
| Colour Rendering (Ra) | 80-89 |
| Colour of Light | White |
| Light colour options | Single Color |
| Including bulb | Yes |
| Driver Included | Yes |

| | |
|--------------------------|--------------------------------|
| Beam Angle (degree) | 60 |
| Luminous Efficacy (lm/W) | 125 |
| Power factor | >0.90 |
| Installation Depth (mm) | 89 |
| Unified Glare Rating | < 19 - for offices and schools |
| Optical Cover | PC (Polycarbonate) |
| Finish of Reflector | PC (Polycarbonate) |
| Product Type Category | LED Downlight |

Fixture Information

| | |
|------------------------|-------------------|
| Mounting Method | Recessed |
| Cut out (mm) | 120 |
| IP-rating | IP20 |
| Impact Protection (IK) | IK03 - 0.35 joule |
| Operating Temperature | -20 to +40 |
| Housing | Aluminium |
| Colour of the Fixture | White |
| Colour of material | White |
| Series | Apollo |

Dimensions

| | |
|---------------|-----|
| Height (mm) | 89 |
| Diameter (mm) | 145 |

 **Sensor Information** Order from the **largest lighting specialist** in Europe  **Customised** quotation

Type of sensor  **Up to 7 years warranty** No Sensor  **Easy** return process